

I claim:

Sub
CH
1. An archery bow including bow speed specific sight pin openings for sight pins located therein relative to each other at fixed distances for a given bow speed, so that when a single sight pin is manually positioned to indicate its corresponding arrow flight range, each of the other sight pins in the other openings will be in position to indicate their corresponding arrow flight ranges.

2. An archery bow as recited in claim 1 including a riser and wherein the sight pin openings are located on a riser.

Sub
CH
3. An archery bow including a bow speed specific sight pin block having sight pin openings for sight pins located therein relative to each other at fixed distances for a given bow speed, so that when a single sight pin is manually positioned to indicate its corresponding arrow flight range, each of the other sight pins in the other openings will be in position to indicate their corresponding arrow flight ranges.

4. An archery bow as recited in claim 3 including a riser and wherein the sight pin block is located on a riser.

5. An archery bow as recited in claim 4 including an opening in the riser and wherein the sight pin block is located in the riser opening.

6. An archery bow as recited in claim 4 wherein the pin block comprises a generally rectangular frame having a generally rectangular opening.

Sub
CH
7. A bow speed specific sight pin block having sight pin openings for sight pins located therein relative to each other at fixed distances for a given bow speed, so that when a single sight pin is manually positioned to indicate its corresponding arrow flight range, each of the other sight pins will be in position to indicate their corresponding arrow flight ranges.

8. An archery bow including a sight pin block mounted therein, said archery bow including a riser having an opening therein, said bowsight pin block being perpendicularly mounted in sidewalls of said opening and said bowsight pin block having at least one moveable wedge which engages one such sidewall for mounting the bowsight pin block in the opening of said riser.

9. An archery bow including a sight pin block as set forth in claim 8 and wherein said bowsight pin block has two moveable wedges which engage one such sidewall for mounting the bowsight pin block in the opening of said riser.

10. An archery bow including a sight pin block as set forth in claim 8 and wherein said bowsight pin block has at least one opening which includes an allen screw therein, and wherein said allen screw moves the wedge to engage a sidewall for mounting the bowsight pin block in the opening of said riser.

11. An archery bow including a bowsight pin block as set forth in claim 9 and wherein said bowsight pin block has two openings therein, each of which includes an allen screw therein, and wherein said allen screws move the wedges to engage one such sidewall for mounting the bowsight pin block in the opening of said riser.

12. An archery bow including a sight pin block as set forth in claim 8 wherein such opening has a recess around the periphery thereof and wherein said bowsight pin block has a raised rib which sits within said recess.

add D7

ADD E7